

GG S06.70 RP6C

Article code: FBGG054790

General information

Product group	High performance flat belts
Product sub type	Classic
Industry segment	Container & packaging; Carton & boxes
Main product feature	High grip, Shock absorbing
Application	Boxfolding, Flexofolders
Indication of use	High efficient rubber cover

Belt construction

Tension member		Polyamide foil
Top side	material	NBR elastomer
	finish	P6 Grip face profile
	color	Light blue
Bottom / Pulley side	material	XNBR elastomer
	finish	Rough
	color	grey

Characteristics

Food Grade (FG)	no	
Antistatic (AS)	yes	ISO 284
High conductive (HC)	no	
ATEX approval	no	

Technical data

Belt thickness	DIN EN ISO 2286-3		7 mm	0.28 in.
	tolerance	±	0.5 mm	0.02 in.
Weight	ISO 290703-1		6.5 kg/m ²	1.33 lbs/ft ²
Force at 1% elongation	DIN EN ISO 21181	dynamic	6 N/mm	34.26 lbs/in.
	DIN EN ISO 527	static	18 N/mm	102.78 lbs/in.
Recommended elongation		min. / max.	2 / 3 %	
Coefficient of friction, dynamic	DIN EN ISO 21182	bottom side to steel	0,6 μ	
		top side to steel	1 μ	
Minimum pulley diameter	flexing		90 mm	3.54 in.
	back flexing		90 mm	3.54 in.
Operating temperature	continuous	from / to	0 / 80 °C	32 / 176 °F
Belt width	standard		570 mm	22.44 in.

Fabrication

WedgeSkive75D-2.8+

-

Additional Information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Consult our specialists for further instructions regarding joining, storage & maintenance, tracking & tensioning.

Consult our specialists for calculations with our E-RappCalc© technical calculation program.

Our material, as well as the packaging, must be disposed of in a professional and environmentally friendly manner.

This item contains the following substance included on the candidate list according to article 59 (1, 10) of Regulation (EC) No 1907/2006 „REACH“ in a concentration above 0.1 % weight by weight: 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol [119-47-1]