

Fabric E郑 10/1 01+0 natural

Article code: ZLFA056427

General information

Product group	ZipLink
Industry segment	Paper & print; Tyre
Main product feature	Hydrolysis resistant, Low friction surface
Indication of use	Slider bed, Rollers, Flat

Belt construction

Tension layer		Ziplink fabric, flexible
Number of plies		1
Top side	material	fabric, fabric
	finish	bare fabric
	color	natural
Bottom side	material	SBR, SBR
	finish	smooth
	color	black

Technical data

Force at 1% elongation	ISO 21181		10 N/mm	57.1 lbs/in.
Thickness	AB method KV.002		3.5 mm	0.14 in.
		top cover	0 mm	0 in.
Weight	AB method KV.004		4 kg/m ²	0.82 lbs/ft ²
Operating temperature	continuous	from / to	-10 / 120 °C	14 / 248 °F
	short	from / to	-10 / 120 °C	14 / 248 °F
Minimum pulley diameter	flexing		60 mm	2.36 in.
	backflexing		100 mm	3.94 in.
Manufacturing width	standard		1300 mm	51.18 in.
	maximum		1300 mm	51.18 in.

Fabrication

Ziplink belts can be endlessed, very easy and quick splicing without presses, fasteners or glues. Refer to the technical information for more information about splicing of Ziplink belts.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.