

# PTFE 100-10 Fibreglass SW

Article code: PPFT000022

## General information

<b>Product group</b>	Peak Products
----------------------	---------------

## Belt construction

<b>Fabric tension layer</b>	Fibreglass
<b>Color</b>	beige

## Characteristics

<b>Food Grade (FG)</b>	yes
<b>Antistatic (AS)</b>	no

## Technical data

<b>Belt thickness</b>			0.254 mm	0.01 in.
<b>Weight</b>			0.325 kg/m <sup>2</sup>	0.07 lbs/ft <sup>2</sup>
<b>Operating temperature</b>	continuous	from / to	-73 / 260 °C	-99.4 / 500 °F
	short	from / to	-73 / 270 °C	-99.4 / 518 °F
<b>Manufacturing length</b>	maximum		100000 mm	3937.01 in.
<b>Manufacturing width</b>	standard		2200 mm	86.61 in.
	maximum		2000 mm	78.74 in.

## Fabrication

<b>Recommended splice method</b>	Peak Products
----------------------------------	---------------

## Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Keep the belt tension to a practical working minimum for maximum belt and machine life.

Store loose and wrapped in plastic. The allowable product temperature may vary.

Consult our specialists in case of questions or remarks.