

# PTFE 100-14 Fibreglass S NL FG

Article code: PPTS000013

## General information

<b>Product group</b>	Peak Products
----------------------	---------------

## Belt construction

<b>Fabric tension layer</b>	Fibreglass
-----------------------------	------------

<b>Color</b>	beige
--------------	-------

## Characteristics

<b>Food Grade (FG)</b>	yes	Yes; Yes; Yes
------------------------	-----	---------------

<b>Antistatic (AS)</b>	no	
------------------------	----	--

## Technical data

<b>Belt thickness</b>			0.3556 mm	0.01 in.
-----------------------	--	--	-----------	----------

<b>Operating temperature</b>	continuous	from / to	-73 / 260 °C	-99.4 / 500 °F
------------------------------	------------	-----------	--------------	----------------

	short	from / to	-73 / 270 °C	-99.4 / 518 °F
--	-------	-----------	--------------	----------------

<b>Manufacturing length</b>	maximum		100000 mm	3937.01 in.
-----------------------------	---------	--	-----------	-------------

<b>Manufacturing width</b>	standard		1000 mm	39.37 in.
----------------------------	----------	--	---------	-----------

	maximum		1000 mm	39.37 in.
--	---------	--	---------	-----------

## Fabrication

<b>Recommended splice method</b>	Peak Products
----------------------------------	---------------

## Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Keep the belt tension to a practical working minimum for maximum belt and machine life.

Store loose and wrapped in plastic. The allowable product temperature may vary.

Consult our specialists in case of questions or remarks.