Technical datasheet

AmSqueeze 316 A18-A18 1605x205x16mm

Article code: EWMS000150

General information

Product group	endless woven
Industry segment	Food: Meat & poultry
Main product feature	Foodgrade, Abrasion resistant, Oil & grease resistant, Cut resistant
Application	Soft Separator
Indication of use	Special fine structured surface, Abrasive applications

Belt construction

Tension layer		polyester
Number of plies		1
Top side	**material**	Ropanyl, TPU
	finish	profile, A18 Fine square profile
	color	ivory
Bottom side	**material**	Ropanyl, TPU
	finish	profile, A18 Fine square profile
	color	white

Characteristics

Food Grade (FG)	yes	EC 1935/2004, EU 10-2011; FDA
Antistatic (AS)	no	
Flame-retardant (FR)	no	

Technical data

Hardness	ISO 868	top side	76A	Shore		
		bottom side	85A	Shore		
Force at 1% elongation	ISO 21181		28	N/mm	159.88	lbs/in.
Thickness		total	16	mm	0.63	in.
		top cover	6.7	mm	0.26	in.
		bottom cover	6.7	mm	0.26	in.
Weight			26.0	kg/m²	5.33	lbs/ft²
Length		from / to	1605	mm		in.
Width		from / to	205	mm		in.
Operating temperature	continuous	from / to	-20 / 90	°C	-4 / 194	°F
	short	from / to	-30 / 110	°C	-22 / 230	°F
Minimum pulley diameter			160	mm	6.3	in.

Tolerances

Length	± 1 %	minimum ±	20	mm	0.79	in.
Width		from / to	-1 / +1	mm	-0.04 / +0.04	in.
Thickness		±	0.2	mm	0.01	in.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.