

Soliflex PRO TPE/20 1mm Si light blue FG Quattro

Article code: SFPE000227

General information

Product group	Soliflex
Main product feature	Positive drive, Chemical resistant, Non-stick, Cold resistant

Belt construction

Material	TPE-E
Top side	smooth
Bottom side	smooth
Color	Light blue

Characteristics

Food Grade (FG)	yes	EU 1935/2004, EU 10/2011; FDA; USDA
------------------------	-----	-------------------------------------

Technical data

Pitch			51 mm	2.01 in.
Hardness	ISO 868		40A Shore	
Force at 1% elongation	ISO 21181		3.6 N/mm	20.56 lbs/in.
Belt thickness			3 mm	0.12 in.
Weight			2.4 kg/m ²	0.49 lbs/ft ²
Operating temperature	continuous	from / to	-20 / 80 °C	-4 / 176 °F
Minimum pulley diameter	flexing		159.8 mm	6.29 in.
	backflexing		192.4 mm	7.57 in.
Manufacturing width	maximum		1200 mm	47.24 in.

Fabrication

Recommended splice method	Butt weld
----------------------------------	-----------

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Keep the belt tension to a practical working minimum for maximum belt and machine life.

Store loose and wrapped in plastic. The allowable product temperature may vary.

