

Nonex EF 15/3 05+05 light blue FG NL

Article code: SBPP4247P2

General information

Product group	Synthetic Belts
Main product feature	Foodgrade, Non logo, Oil & grease resistant

Belt construction

Number of plies		3
Top side	material	Nonex, PVC
	finish	smooth, glossy
	color	Light blue
Bottom side	material	Nonex, PVC
	finish	matt, M2 Matt finish
	color	Light blue

Characteristics

Food Grade (FG)	yes	FDA
Antistatic (AS)	no	
High conductive (HC)	no	
ATEX approval	no	

Technical data

Force at 1% elongation (static)	ISO 21181		15 N/mm	85.65 lbs/in.
Thickness	AB method KV.002	total	3.7 mm	0.15 in.
		top cover	0.5 mm	0.02 in.
Weight	AB method KV.004		4.2 kg/m ²	0.86 lbs/ft ²
Manufacturing width	standard		2000 mm	78.74 in.
	maximum		2000 mm	78.74 in.

Fabrication

Hot splicing is always preferable. Glueing can only be done when the belt is exposed to normal temperature and the humidity is not excessive.

For the working method, consult the splice information and the equipment literature. Apply the recommended splice as indicated in the separate information.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.