

PU Torque XH Steel NT

Article code: TBUT102310

General information

Productgroup	Timing belts, PU Torque
Industry segment	General industry; Wood; Building materials: Stone & ceramics, Bricks & tiles
Main product feature	Low friction tooth side, Positive drive, Wear resistant bottom side

Belt construction

Tension member		steel
Material	body	Polyurethane
Surface	tooth side	Polyamide fabric
	back side	Polyurethane

Characteristics


Food Grade (FG)	no
Antistatic (AS)	no
Oil & Fat resistance	yes

Technical data


Tooth	profile		XH		
	pitch		22.225 mm	0.87 in.	
Hardness body material	ISO 868		92A Shore		
Belt thickness			11.2 mm	0.44 in.	
Belt weight			10.6 kg/m ²	2.17 lbs/ft ²	
Coefficient of friction	tooth side to steel	dynamic	0,3		
Operating temperature	continuous	from / to	-10 / 80 °C	14 / 176 °F	
Minimum pulley diameter	A) without counter flexing	number of teeth, t1	18		
		d1	124.54 mm	4.9 in.	
		d2	150 mm	5.91 in.	
	B) with counter flexing	number of teeth, t1	20		
		d1	138.69 mm	5.46 in.	
		d2	180 mm	7.09 in.	
Belt width	maximum		150 mm	5.91 in.	
Belt length	minimum		900 mm	35.43 in.	
	maximum		25000 mm	82.02 ft.	

Reference images


Side view



A) without counter flexing



B) with counter flexing



Fabrication

This information on the fabrication options is general, please contact Ammeraal Beltech to inquire for the specific fabrication possibilities of the timing belt of your choice.

Cleats welded or mechanically attached, metal teeth, guides welded or glued.

Covers can be welded, glued, coated or vulkanized onto the back side of the timing belt.

Thermoplastic covers can be embossed.

Perforations, lateral and logitudinal slots, lateral and longitudinal profiles.

Additional Information

Tooth profile according to standard: metric ISO 17396 , imperial ISO 5296-1, curvilinear ISO 13050, depending on the belt type.

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Consult our specialists for further information like technical calculations. Instructions regarding joining, storage & maintenance and tracking & tensioning.

Standard belt width [mm]	Allow. tensile load Linear open end & Torque [N]	Allow. tensile load Linear welded endless [N]		Spring force [N]
25.4	3200	1600		880000
50.8	6500	3250		1760000
76.2	9800	4900		2640000
101.61	13500	6750		3520000

Speed rpm [1/min]	Specific tooth force [N/mm]	Specific power [W/mm]	
0	9.6	0	
25	9.266	0.086	
50	8.953	0.166	
75	8.67	0.241	
100	8.383	0.311	
150	7.926	0.44	
200	7.48	0.554	
300	6.942	0.771	
400	6.553	0.971	
500	6.248	1.157	
750	5.691	1.581	
1000	5.288	1.959	
1250	4.977	2.304	
1500	4.719	2.622	
1750	4.502	2.918	
2000	4.314	3.196	
3000	3.74	4.156	
4000	3.331	4.935	

Standard	