

PTFE DXL-10 Fibreglass

Article code: PPFD000005

General information

| | |
|---------------|---------------|
| Product group | Peak Products |
|---------------|---------------|

Belt construction

| | |
|----------------------|------------|
| Fabric tension layer | Fibreglass |
| Color | Copper |

Characteristics

| | | |
|-----------------|-----|---------------|
| Food Grade (FG) | yes | Yes; Yes; Yes |
| Antistatic (AS) | no | |

Technical data

| | | | | |
|-----------------------|------------|-----------|-------------------------|--------------------------|
| Belt thickness | | | 0.254 mm | 0.01 in. |
| Weight | | | 0.522 kg/m ² | 0.11 lbs/ft ² |
| PTFE content | | | 79.2 % | |
| Operating temperature | continuous | from / to | -73 / 260 °C | -99.4 / 500 °F |
| | short | from / to | -73 / 300 °C | -99.4 / 572 °F |
| Manufacturing length | maximum | | 100000 mm | 3937.01 in. |
| Manufacturing width | standard | | 1000 mm | 39.37 in. |
| | maximum | | 1500 mm | 59.06 in. |

Fabrication

| | |
|---------------------------|---------------|
| Recommended splice method | Peak Products |
|---------------------------|---------------|

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Keep the belt tension to a practical working minimum for maximum belt and machine life.

Store loose and wrapped in plastic. The allowable product temperature may vary.

Consult our specialists in case of questions or remarks.