

Amtel EM 4/1 00+03 ivory M1 FG NL

Article code: SBRP0278A1

General information

Product group Synthetic Belts

Belt construction

Tension layer		polyester, stable
Number of plies		1
Top side	material	Amtel, TPE-E
	finish	smooth, M1 Fine matt finish
	color	ivory
Bottom side	material	Ropanol, PUR
	finish	impregnated fabric
	color	natural

Characteristics

Food Grade (FG)	yes	EC 1935/2004, EU 10/2011; FDA
Antistatic (AS)	no	
High conductive (HC)	no	
ATEX approval	no	

Technical data

Hardness	ISO 868	top side	40D Shore		
Force at 1% elongation (static)	ISO 21181		4 N/mm	22.84 lbs/in.	
Thickness	AB method KV.002	total	0.8 mm	0.03 in.	
		top cover	0.3 mm	0.01 in.	
Weight	AB method KV.004		0.9 kg/m ²	0.18 lbs/ft ²	
Operating temperature	continuous	from / to	-20 / 110 °C	-4 / 230 °F	
	short	from / to	-30 / 130 °C	-22 / 266 °F	
Manufacturing width	standard		1600 mm	62.99 in.	

Fabrication

Hot splicing is always preferable. Glueing can only be done when the belt is exposed to normal temperature and the humidity is not excessive.

For the working method, consult the splice information and the equipment literature. Apply the recommended splice as indicated in the separate information.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.