

Solicord V-belt TPU 75A Sky Blue SM FG 10x6

Article code: SCVB000189

General information

Product group SoliCord

Construction

Material TPU
(Top)surface finish smooth
Color sky blue
Shape Vee
Execution solid

Characteristics

Food Grade (FG) yes all foodstuff; all foodstuff
Antistatic (AS) no
ATEX approval no

Technical data

Hardness	ISO 868		75A Shore	
Recommended pre-tension			7 %	
Working tension			13 daN/cm ²	
Diameter			0 mm	0 in.
Cross section			0.48 cm ²	
Weight			0.06 kg/m	0.01 lb/ft
Operating temperature	continuous	from / to	-30 / 80 °C	-22 / 176 °F
Minimum pulley diameter			50 mm	1.97 in.
Coefficient of friction	against steel	dynamic	0,7	
	against PE		0,4	
	against HDPE		0,35	
Manufacturing length	maximum		50000 mm	1968.5 in.

Fabrication

Recommended splice types Butt weld
Splice equipment Only use equipment supplied or approved by Ammeraal Beltech.
Splicing on site Always first make a test splice to confirm the right settings and proper pre-heating of the equipment.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.
 Keep the belt tension to a practical working minimum for maximum belt and machine life.
 Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt.