

# Solicord Round twisted TPU 85A Transp SM FG 60 560

Article code: SCRB000422

## General information

|               |          |
|---------------|----------|
| Product group | SoliCord |
|---------------|----------|

## Construction

|                     |             |
|---------------------|-------------|
| Material            | TPU         |
| (Top)surface finish | smooth      |
| Color               | transparent |
| Shape               | round       |
| Execution           | solid       |

## Characteristics

|                 |     |                              |
|-----------------|-----|------------------------------|
| Food Grade (FG) | yes | all foodstuff; all foodstuff |
| Antistatic (AS) | no  |                              |
| ATEX approval   | no  |                              |

## Technical data

|                         |               |           |             |  |              |
|-------------------------|---------------|-----------|-------------|--|--------------|
| Hardness                | ISO 868       |           | 85A Shore   |  |              |
| Recommended pre-tension |               |           | 8-10 %      |  |              |
| Diameter                |               |           | 5 mm        |  | 0.2 in.      |
| Weight                  |               |           | 0.0336 kg/m |  | 0.01 lb/ft   |
| Operating temperature   | continuous    | from / to | -30 / 80 °C |  | -22 / 176 °F |
| Minimum pulley diameter |               |           | 40 mm       |  | 1.57 in.     |
| Coefficient of friction | against steel | dynamic   | 0,65        |  |              |
|                         | against PE    |           | 0,35        |  |              |
|                         | against HDPE  |           | 0,3         |  |              |
| Manufacturing length    | maximum       |           | 30000 mm    |  | 1181.1 in.   |

## Fabrication

|                          |                                                                                                        |
|--------------------------|--------------------------------------------------------------------------------------------------------|
| Recommended splice types | hook                                                                                                   |
| Splice equipment         | Only use equipment supplied or approved by Ammeraal Beltech.                                           |
| Splicing on site         | Always first make a test splice to confirm the right settings and proper pre-heating of the equipment. |

## Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Keep the belt tension to a practical working minimum for maximum belt and machine life.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt.