

# PTFE 100-05 Fibreglass TR

Article code: PPFT000017

## General information

|                      |               |
|----------------------|---------------|
| <b>Product group</b> | Peak Products |
|----------------------|---------------|

## Belt construction

|                             |            |
|-----------------------------|------------|
| <b>Fabric tension layer</b> | Fibreglass |
| <b>Color</b>                | beige      |

## Characteristics

|                        |     |
|------------------------|-----|
| <b>Food Grade (FG)</b> | yes |
| <b>Antistatic (AS)</b> | no  |

## Technical data

|                              |            |           |                         |                          |
|------------------------------|------------|-----------|-------------------------|--------------------------|
| <b>Belt thickness</b>        |            |           | 0.127 mm                | 0 in.                    |
| <b>Weight</b>                |            |           | 0.258 kg/m <sup>2</sup> | 0.05 lbs/ft <sup>2</sup> |
| <b>Operating temperature</b> | continuous | from / to | -73 / 260 °C            | -99.4 / 500 °F           |
|                              | short      | from / to | -73 / 270 °C            | -99.4 / 518 °F           |
| <b>Manufacturing length</b>  | maximum    |           | 100000 mm               | 3937.01 in.              |
| <b>Manufacturing width</b>   | standard   |           | 1000 mm                 | 39.37 in.                |
|                              | maximum    |           | 1000 mm                 | 39.37 in.                |

## Fabrication

|                                  |               |
|----------------------------------|---------------|
| <b>Recommended splice method</b> | Peak Products |
|----------------------------------|---------------|

## Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Keep the belt tension to a practical working minimum for maximum belt and machine life.

Store loose and wrapped in plastic. The allowable product temperature may vary.

Consult our specialists in case of questions or remarks.