

## PG E05.12 SFQ

Article code: FBPG054630

### General information

<b>Product group</b>	High performance flat belts
<b>Product sub type</b>	QuickSplice
<b>Industry segment</b>	Paper & print; Postal automation
<b>Main product feature</b>	Abrasion resistant, High grip, Low friction surface
<b>Application</b>	Paper processing, Printing & finishing, Mail handling
<b>Indication of use</b>	Bi-directional, High efficient rubber cover

### Belt construction

<b>Tension member</b>		Polyester fabric
<b>Top side</b>	<b>material</b>	XNBR elastomer
	<b>finish</b>	Fine
	<b>color</b>	green
<b>Bottom / Pulley side</b>	<b>material</b>	Thermoplastic elastomere
	<b>finish</b>	smooth
	<b>color</b>	black

### Characteristics

<b>Food Grade (FG)</b>	no	
<b>Antistatic (AS)</b>	yes	
<b>High conductive (HC)</b>	no	

### Technical data

<b>Belt thickness</b>	ISO 2286-3		1.2 mm	0.05 in.
<b>Weight</b>	ISO 290703-1		1.2 kg/m <sup>2</sup>	0.25 lbs/ft <sup>2</sup>
<b>Force at 1% elongation</b>	ISO 21181	dynamic	5 N/mm	28.55 lbs/in.
<b>Recommended elongation</b>		min. / max.	0.5 / 2 %	
<b>Coefficient of friction, dynamic</b>	ISO 21182	bottom side to steel	0,2	
		top side to steel	0,5	
<b>Minimum pulley diameter</b>	flexing		20 mm	0.79 in.
	back flexing		20 mm	0.79 in.
<b>Operating temperature</b>	continuous	from / to	0 / 60 °C	32 / 140 °F
<b>Belt width</b>	standard		480 mm	18.9 in.

### Fabrication

<b>Recommended splice method</b>	QuickSplice50
<b>Alternative splice method</b>	QuickSplice30

### Fabrication

QuickSplice50
QuickSplice30

### Additional Information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Consult our specialists for further instructions regarding joining, storage & maintenance, tracking & tensioning.

Consult our specialists for calculations with our E-RappCalc© technical calculation program.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.