

PTFE 100-10 Fibreglass S NL FG

Article code: PPTS000012

General information

| | |
|----------------------|---------------|
| Product group | Peak Products |
|----------------------|---------------|

Belt construction

| | |
|-----------------------------|------------|
| Fabric tension layer | Fibreglass |
| Color | beige |

Characteristics

| | | |
|------------------------|-----|---------------|
| Food Grade (FG) | yes | Yes; Yes; Yes |
| Antistatic (AS) | no | |

Technical data

| | | | | |
|------------------------------|------------|-----------|-------------------------|-------------------------|
| Belt thickness | | | 0.254 mm | 0.01 in. |
| Weight | | | 0.488 kg/m ² | 0.1 lbs/ft ² |
| Operating temperature | continuous | from / to | -73 / 260 °C | -99.4 / 500 °F |
| | short | from / to | -73 / 270 °C | -99.4 / 518 °F |
| Manufacturing length | maximum | | 100000 mm | 3937.01 in. |
| Manufacturing width | standard | | 1000 mm | 39.37 in. |
| | maximum | | 1000 mm | 39.37 in. |

Fabrication

| | |
|----------------------------------|---------------|
| Recommended splice method | Peak Products |
|----------------------------------|---------------|

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Keep the belt tension to a practical working minimum for maximum belt and machine life.

Store loose and wrapped in plastic. The allowable product temperature may vary.

Consult our specialists in case of questions or remarks.