

MSB329 AmSqueeze 714 A93-A93

1330x205x13.4mm

Article code: EWMS000377

General information

Product group	endless woven
Industry segment	Food: Meat & poultry
Main product feature	Foodgrade, Abrasion resistant, Oil & grease resistant, Cut resistant
Application	Soft Separator
Indication of use	Special fine structured surface, Abrasive applications

Belt construction

Tension layer		polyester
Number of plies		1
Top side	material	Ropanyl, TPU
	finish	profile, A93-Rhombus
	color	transparent
Bottom side	material	Ropanyl, TPU
	finish	profile, A93-Rhombus
	color	white

Characteristics

Food Grade (FG)	yes	EC 1935/2004, EU 10-2011; FDA
Antistatic (AS)	no	
Flame-retardant (FR)	no	

Technical data

Hardness	ISO 868	top side	93A Shore	
		bottom side	85A Shore	
Force at 1% elongation	ISO 21181		28 N/mm	159.88 lbs/in.
Thickness		total	13.4 mm	0.53 in.
		top cover	5.4 mm	0.21 in.
		bottom cover	5.4 mm	0.21 in.
Weight			21.8 kg/m ²	4.46 lbs/ft ²
Length		from / to	1330 mm	in.
Width		from / to	205 mm	in.
Operating temperature	continuous	from / to	-20 / 90 °C	-4 / 194 °F
	short	from / to	-30 / 110 °C	-22 / 230 °F
Minimum pulley diameter			134 mm	5.28 in.

Tolerances

Length	± 1 %	minimum ±	20 mm	0.79 in.
Width		from / to	-0 / +2 mm	-0 / +0.08 in.
Thickness		±	0.2 mm	0.01 in.

Side view



Belt type	AmSqueeze 300 series	AmSqueeze 500 series	AmSqueeze 700 series
Example article description	AS 314 A93-A93	AS 514 A93-A93	AS 714 A93-A93
Top cover material	TPU 3 mm Ropanyl FG	TPU 3 mm Ropanyl FG	TPU 3 mm Ropanyl FG
Top cover color	Ivory	White	Transparent
Top cover hardness	76° Shore A	85° Shore A	93° Shore A
Standard finish covers	A93 Rhombus profile	A93 Rhombus profile	A93 Rhombus profile
Standard belt thickness	13.4	13,4	13.4
Other available belt thickness [mm]	15,16,17,18,19,20	15,16,17,18	15,16,17,18
Grip	+++++	++++	+++
Wear resistance	+++	++++	+++++
Yield	+++++	++++	+++
Food Grade	EC/FDA	EC/FDA	EC/FDA

Consult our application engineers and product information for other options.
Tolerance on length $\pm 1\%$ Width $-0/+2$ mm.
Closed edges skived.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.