## Soliflex TPU/20 1mm Si light blue FG

Ammeraal Beltech
Innovation & Service in Belting

Article code: SFPU000756

General information	
Product group	Soliflex
Belt construction	
Material	TPU
Top side	M1 Fine matt finish
Bottom side	smooth
Color	Light blue

Characteristics		
Food Grade (FG)	yes	EU 1935/2004, EU 10/2011; FDA; USDA

Technical data						
Hardness	ISO 868		40A	Shore		
Force at 1% elongation	ISO 21181		2	N/mm	11.42	lbs/in.
Belt thickness			3	mm	0.12	in.
Weight			2.4	kg/m²	0.49	lbs/ft²
Operating temperature	continuous	from / to	-5 / 70	°C	23 / 158	°F
Minimum pulley diameter	flexing		80	mm	3.15	in.
	backflexing		120	mm	4.72	in.
Manufacturing width	maximum		1800	mm	70.87	in.

Fabrication	
Recommended splice method	Butt weld

## **Additional information**

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ. Keep the belt tension to a practical working minimum for maximum belt and machine life.

Store loose and wrapped in plastic. The allowable product temperature may vary.