**Technical datasheet** 

## PTFE KEV Mesh K76-250 4x4



Article code: PPFK000002

General information					
Product group	Peak Products	Peak Products			
Belt construction					
Fabric tension layer	aramid				
Color	Straw				
Characteristics					
Food Grade (FG)	yes	Yes; Yes; Yes			
Antistatic (AS)	no				

Technical data						
Belt thickness			0.76 m	nm	0.03	in.
Weight			0.25 k	g/m²	0.05	lbs/ft²
PTFE content			40 %	6		
Operating temperature	continuous	from / to	-73 / 260 °C	С	-99.4 / 500	°F
	short	from / to	-73 / 300 °C	С	-99.4 / 572	°F
Manufacturing length	maximum		100000 m	nm	3937.01	in.
Manufacturing width	standard		2600 m	nm	102.36	in.
	maximum		5000 m	nm	196.85	in.

Fabrication	
Recommended splice method	Peak Products

## **Additional information**

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Keep the belt tension to a practical working minimum for maximum belt and machine life.

Store loose and wrapped in plastic. The allowable product temperature may vary.

Consult our specialists is case of questions or remarks.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.