

# Ultraclean EZP 8/1 0+0 light blue

Article code: ZLFA583064

## General information

<b>Product group</b>	Ziplink
<b>Industry segment</b>	Wood
<b>Indication of use</b>	Flat, Rollers, Slider bed

## Belt construction

<b>Tension layer</b>		Ziplink fabric, flexible
<b>Number of plies</b>		1
<b>Top side</b>	<b>material</b>	Ultraclean, PTFE
	<b>finish</b>	bare fabric
	<b>color</b>	Light blue
<b>Bottom side</b>	<b>material</b>	ultraclean, PTDE
	<b>finish</b>	bare fabric
	<b>color</b>	Light blue

## Technical data

<b>Force at 1% elongation</b>	ISO 21181		8 N/mm	45.68 lbs/in.
<b>Thickness</b>	AB method KV.002		2 mm	0.08 in.
		top cover	0 mm	0 in.
<b>Weight</b>	AB method KV.004		1.4 kg/m <sup>2</sup>	0.29 lbs/ft <sup>2</sup>
<b>Operating temperature</b>	continuous	from / to	-40 / 180 °C	-40 / 356 °F
	short	from / to	-40 / 180 °C	-40 / 356 °F
<b>Minimum pulley diameter</b>	flexing		16 mm	0.63 in.
	backflexing		20 mm	0.79 in.
<b>Manufacturing width</b>	standard		4000 mm	157.48 in.
	maximum		5000 mm	196.85 in.

## Fabrication

Ziplink belts can be endlessed, very easy and quick splicing without presses, fasteners or glues. Refer to the technical information for more information about splicing of Ziplink belts.

## Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.