Technical datasheet

Fabric EZP 8/1 0+0 red HR

Article code: ZLFA583063



General information	
Product group	ZipLink
Industry segment	Wood
Main product feature	Heat resistant

Belt construction				
Tension layer		Ziplink fabric, flexible		
Number of plies		1		
Top side	material	fabric, polyester		
	finish	bare fabric		
	color	red		
Bottom side	material	Mesh, polyester		
	finish	bare fabric		
	color	red		

Characteristics			
Antistatic (AS)	yes		

Technical data						
Force at 1% elongation	ISO 21181		8	N/mm	45.68	lbs/in.
Thickness	AB method KV.002		1.9	mm	0.07	in.
Weight	AB method KV.004		1.75	kg/m²	0.36	lbs/ft²
Operating temperature	continuous	from / to	-40 / 180	°C	-40 / 356	°F
	short	from / to	-40 / 180	°C	-40 / 356	°F
Manufacturing width	standard		3300	mm	129.92	in.
	maximum		3800	mm	149.61	in.

Fabrication

Ziplink belts can be endlessed, very easy and quick splicing without presses, fasteners or glues. Refer to the technical information for more information about splicing of Ziplink belts.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ. We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.

Because of continuous development, the presented data is subject to alteration. This data above stated information. Subject to the general terms and conditions of sale and delivery	replaces that included in previous publication y, as applied by its operating companies, are	ns. Ammeraal Beltech excludes any liability all activities performed and services render	for the incorrect use of the ed by Ammeraal Beltech.