

# UU E15.20 RFQ

Article code: FBUE054765

## General information

<b>Product group</b>	High performance flat belts
<b>Product sub type</b>	QuickSplice
<b>Industry segment</b>	Logistics
<b>Main product feature</b>	Low friction surface
<b>Application</b>	Roller drives
<b>Indication of use</b>	Bi-directional

## Belt construction

<b>Tension member</b>		Polyester fabric
<b>Top side</b>	<b>material</b>	Polyurethane
	<b>finish</b>	Fine
	<b>color</b>	black
<b>Bottom / Pulley side</b>	<b>material</b>	Polyurethane
	<b>finish</b>	Rough
	<b>color</b>	black

## Characteristics

<b>Food Grade (FG)</b>	no	
<b>Antistatic (AS)</b>	yes	
<b>High conductive (HC)</b>	no	

## Technical data

<b>Belt thickness</b>	ISO 2286-3		2 mm	0.08 in.
<b>Weight</b>	ISO 290703-1		2.2 kg/m <sup>2</sup>	0.45 lbs/ft <sup>2</sup>
<b>Force at 1% elongation</b>	ISO 21181	dynamic	15 N/mm	85.65 lbs/in.
<b>Recommended elongation</b>		min. / max.	0.5 / 1.5 %	
<b>Coefficient of friction, dynamic</b>	ISO 21182	bottom side to steel	0,2	
		top side to steel	0,2	
<b>Minimum pulley diameter</b>	flexing		25 mm	0.98 in.
	back flexing		25 mm	0.98 in.
<b>Operating temperature</b>	continuous	from / to	0 / 60 °C	32 / 140 °F
<b>Belt width</b>	standard		1200 mm	47.24 in.

## Fabrication

<b>Recommended splice method</b>	QuickSplice110
<b>Alternative splice method</b>	QuickSplice50

## Fabrication

QuickSplice110
QuickSplice50

## Additional Information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Consult our specialists for further instructions regarding joining, storage & maintenance, tracking & tensioning.

Consult our specialists for calculations with our E-RappCalc© technical calculation program.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.