

Soliflex PRO mini TPU/15 white FG Mono

Article code: SFPU000752

General information

Product group	Soliflex
Main product feature	Positive drive, Chemical resistant, Non-stick, Wear resistant

Belt construction

Material	TPU
Top side	smooth
Bottom side	M1 Fine matt finish
Color	white

Characteristics

Food Grade (FG)	yes	EU 1935/2004, EU 10/2011; FDA; USDA
------------------------	-----	-------------------------------------

Technical data

Pitch			25.5 mm	1 in.
Hardness	ISO 868		53D Shore	
Force at 1% elongation	ISO 21181		1.1 N/mm	6.28 lbs/in.
Belt thickness			1.5 mm	0.06 in.
Weight			1.8 kg/m ²	0.37 lbs/ft ²
Operating temperature	continuous	from / to	-5 / 70 °C	23 / 158 °F
Minimum pulley diameter	flexing		47 mm	1.85 in.
	backflexing		63.3 mm	2.49 in.
Manufacturing width	maximum		1200 mm	47.24 in.

Fabrication

Recommended splice method	Butt weld
----------------------------------	-----------

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Keep the belt tension to a practical working minimum for maximum belt and machine life.

Store loose and wrapped in plastic. The allowable product temperature may vary.

