

S02 C

Article code: FBSF054500

General information

Product group	High performance flat belts
Product sub type	Classic
Industry segment	General industry

Belt construction

Tension member		Polyamide foil
Top side	material	Polyamide foil
	finish	smooth
	color	transparent
Bottom / Pulley side	material	Polyamide foil
	finish	smooth
	color	transparent

Characteristics

Food Grade (FG)	no	
Antistatic (AS)	no	
High conductive (HC)	no	
ATEX approval	no	

Technical data

Belt thickness	ISO 2286-3		0.22 mm	0.01 in.
Weight	ISO 290703-1		0.3 kg/m ²	0.06 lbs/ft ²
Force at 1% elongation	ISO 21181	dynamic	2 N/mm	11.42 lbs/in.
Recommended elongation		from / to	2 / 3 %	
Coefficient of friction, dynamic	ISO 21182	bottom side to steel	0,1 μ	
		top side to steel	0,1 μ	
Minimum pulley diameter	flexing		20 mm	0.79 in.
	back flexing		20 mm	0.79 in.
Operating temperature	continuous	from / to	0 / 80 °C	32 / 176 °F
Belt width	standard		630 mm	24.8 in.

Fabrication

Recommended splice method	WedgeSkive75D-0.5-1.4
----------------------------------	-----------------------

Additional Information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Consult our specialists for further instructions regarding joining, storage & maintenance, tracking & tensioning.

Consult our specialists for calculations with our E-RappCalc® technical calculation program.

Our material, as well as the packaging, must be disposed of in a professional and environmentally friendly manner.