

# Solicord V BELT TPU 85A green SGPVC40 13x8

Article code: SCVB000180

## General information

Product group	SoliCord
---------------	----------

## Construction

Material	TPU
(Top)surface finish	supergrip
Color	green
Shape	vee
Execution	solid

## Characteristics

Food Grade (FG)	no
Antistatic (AS)	no
ATEX approval	no

## Technical data

Hardness	ISO 868		88A Shore	
Recommended pre-tension			2-4 %	
Weight			0.1 kg/m	0.02 lb/ft
Operating temperature	continuous	from / to	-30 / 80 °C	-22 / 176 °F
Minimum pulley diameter			150 mm	5.91 in.
Coefficient of friction	against steel	dynamic	0,45	
	against PE		0,3	
	against HDPE		0,25	
Manufacturing length	maximum		50000 mm	1968.5 in.

## Fabrication

Recommended splice types	Butt weld
Splice equipment	Only use equipment supplied or approved by Ammeraal Beltech.
Splicing on site	Always first make a test splice to confirm the right settings and proper pre-heating of the equipment.

## Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Keep the belt tension to a practical working minimum for maximum belt and machine life.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt.