

UV N12 FQ

Article code: FBUV054557

General information

Product group	High performance flat belts
Product sub type	QuickSplice
Industry segment	Paper & print; Postal automation
Main product feature	Elastic
Application	Paper processing, Printing & finishing, Mail handling
Indication of use	Bi-directional, Gentle cover for delicate papers

Belt construction

Tension member		Polyurethane
Top side	material	Fleece
	finish	Ground quality
	color	grey
Bottom / Pulley side	material	Polyurethane
	finish	Fine
	color	blue

Characteristics

Food Grade (FG)	no	
Antistatic (AS)	yes	
High conductive (HC)	no	

Technical data

Belt thickness	ISO 2286-3		1.5 mm	0.06 in.
Weight	ISO 290703-1		1.7 kg/m ²	0.35 lbs/ft ²
Force at 6% elongation	ISO 21181	dynamic	1.2 N/mm	6.85 lbs/in.
	ISO 527	static	4 N/mm	22.84 lbs/in.
Recommended elongation		min. / max.	0.5 / 1.5 %	
Coefficient of friction, dynamic	ISO 21182	bottom side to steel	0,2	
		top side to steel	0,2	
Minimum pulley diameter	flexing		20 mm	0.79 in.
	back flexing		20 mm	0.79 in.
Operating temperature	continuous	from / to	0 / 60 °C	32 / 140 °F
Belt width	standard		570 mm	22.44 in.

Fabrication

Recommended splice method	QuickSplice30
----------------------------------	---------------

Fabrication

QuickSplice30

Additional Information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Consult our specialists for further instructions regarding joining, storage & maintenance, tracking & tensioning.

Consult our specialists for calculations with our E-RappCalc© technical calculation program.