

# Top compression belt Pletex Red x16.0

Article code: EBC0000001

## General information

<b>Product group</b>	Engineered belts, Compression Belt
<b>Industry segment</b>	Paper & print: Corrugated board
<b>Main product feature</b>	Soft-grip

## Belt specifics

<b>Previous AB Item number</b>	CMM202
--------------------------------	--------

## Belt construction

<b>Base belt or substrate</b>	<b>type</b>	Synthetic belt	
	<b>tensionmember</b>	polyester fabric	
	<b>number of plies</b>	2	
<b>Intermediate layer</b>	<b>material</b>	polyurethane foam	
<b>Belt cover</b>	<b>material</b>	Pletex, thermoplastic polyblend	
	<b>hardness</b>	35A	Shore
	<b>color</b>	red	


## Characteristics

<b>Foodgrade (FG)</b>	<b>cover material</b>	no	
<b>Oil &amp; fat resistant</b>		no	

## Technical data

<b>Belt</b>	<b>thickness</b>		16 mm	0.63 in.
	<b>length</b>	minimum	2500 mm	98.43 in.
		maximum	15000 mm	590.55 in.
	<b>width</b>	minimum	900 mm	35.43 in.
		maximum	1790 mm	70.47 in.
<b>Coefficient of friction</b>	<b>tooth side to steel</b>	dynamic	0,5	
<b>Operating temperature</b>	<b>continuous</b>	from / to	0 / 50 °C	32 / 122 °F
<b>Minimum pulley diameter</b>	<b>flexing</b>		160 mm	6.3 in.
	<b>backflexing</b>		not advised	

## General information



## Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.