

Top compression belt Pletex Red x16.0

Article code: EBC0000001

General information

Product group	Engineered belts, Compression Belt
Industry segment	Paper & print: Corrugated board
Main product feature	Soft-grip

Belt specifics

Previous AB Item number	CMM202
--------------------------------	--------

Belt construction

Base belt or substrate	type	Synthetic belt	
	tensionmember	Polyester fabric	
	number of plies	2	
Intermediate layer	material	polyurethane foam	
Belt cover	material	Pletex, thermoplastic polyblend	
	hardness	35A	Shore
	color	red	


Characteristics

Foodgrade (FG)	cover material	no	
Oil & fat resistant		no	

Technical data

Belt	thickness		16 mm	0.63 in.
	length	minimum	2500 mm	98.43 in.
		maximum	15000 mm	590.55 in.
	width	minimum	900 mm	35.43 in.
		maximum	1790 mm	70.47 in.
Coefficient of friction	tooth side to steel	dynamic	0,5	
Operating temperature	continuous	from / to	0 / 50 °C	32 / 122 °F
Minimum pulley diameter	flexing		160 mm	6.3 in.
	backflexing		not advised	

General information



Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.