

# Fabric E郑 8/1 0+0 red HR

Article code: ZLFA583062

## General information

<b>Product group</b>	ZipLink
<b>Industry segment</b>	Wood
<b>Main product feature</b>	Heat resistant
<b>Indication of use</b>	Slider bed, Rollers, Flat

## Belt construction

<b>Tension layer</b>		Ziplink fabric, flexible
<b>Number of plies</b>		1
<b>Top side</b>	<b>material</b>	fabric, polyester
	<b>finish</b>	bare fabric
	<b>color</b>	red
<b>Bottom side</b>	<b>material</b>	Mesh, polyester
	<b>finish</b>	bare fabric
	<b>color</b>	red

## Characteristics

<b>Antistatic (AS)</b>	yes
------------------------	-----

## Technical data

<b>Force at 1% elongation</b>	ISO 21181		8 N/mm	45.68 lbs/in.
<b>Thickness</b>	AB method KV.002		1.9 mm	0.07 in.
<b>Weight</b>	AB method KV.004		1.75 kg/m <sup>2</sup>	0.36 lbs/ft <sup>2</sup>
<b>Operating temperature</b>	continuous	from / to	-40 / 180 °C	-40 / 356 °F
	short	from / to	-40 / 180 °C	-40 / 356 °F
<b>Manufacturing width</b>	standard		3300 mm	129.92 in.
	maximum		3800 mm	149.61 in.

## Fabrication

Ziplink belts can be endlessed, very easy and quick splicing without presses, fasteners or glues. Refer to the technical information for more information about splicing of Ziplink belts.

## Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.