

# Solicord V-belt TPE 55D Blue SM FG 8x5

Article code: SCVB000023

## General information

Product group	SoliCord
---------------	----------

## Construction

Material	TPE
(Top)surface finish	smooth
Color	blue
Shape	Vee
Execution	solid

## Characteristics

Food Grade (FG)	yes	all foodstuff; all foodstuff
Antistatic (AS)	no	
ATEX approval	no	

## Technical data

Hardness	ISO 868		55D Shore		
Recommended pre-tension			3 %		
Working tension			50 daN/cm <sup>2</sup>		
Diameter			0 mm		0 in.
Cross section			0.32 cm <sup>2</sup>		
Weight			0.04 kg/m		0.01 lb/ft
Operating temperature	continuous	from / to	-30 / 100 °C		-22 / 212 °F
Minimum pulley diameter			80 mm		3.15 in.
Coefficient of friction	against steel	dynamic	0,35		
	against PE		0,15		
	against HDPE		0,1		
Manufacturing length	maximum		50000 mm		1968.5 in.

## Fabrication

Recommended splice types	Butt weld
Splice equipment	Only use equipment supplied or approved by Ammeraal Beltech.
Splicing on site	Always first make a test splice to confirm the right settings and proper pre-heating of the equipment.

## Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Keep the belt tension to a practical working minimum for maximum belt and machine life.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt.