SIDE FLEXING


# EN

# uni Flex Plastic Chain

# Ammeraal Beltech

Series uni 2800 Type -





### uni Flex Plastic Chain

Side flexing chain Pitch: 82.5 mm (3.25 in) Backflex radius: 75.0 mm (2.90 in) Permissible tensile strength: POM material: 6000 N (1349 lbf)

Standard shipping lengths: boxes of 74 links = 6.105 m (20.0 ft)

E		(	5	Ī	•	V		
mm	in	mm	in	mm	in	mm	in	
9.5	0.37	54.0	2.13	82.5	3.25	37.3	1.47	

All dimensions are for chains in POM material.

Width (W)		Material & color	Pin material	Wei	ght	Min. radius (R)		
mm	in	Material & Color	riii iliateriai	kg/m	lb/ft	mm	in	
53.5	2.11	POM-D <b>W</b>	SS304	1.6	1.09	500	19.69	

Non standard material and color: See uni Material and Color Overview. Non standard pin material: See uni Material and Color Overview.




Sprocket															
No of teeth	Pitch diameter		Overall- diameter		Min. ø bore		Max. ø bore		Hub- diameter		Dimension A		Dimension B		led PA6 N
	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	Machined
<b>Z6</b>	165.0	6.50	168.0	6.60	20.0	0.80	40.0	1.60	63.0	2.50	53.0	2.10	101.0	4.00	1
Z8	215.6	8.49	224.0	8.80	20.0	0.80	50.0	2.00	73.5	2.90	81.1	3.20	126.3	5.00	1
Z10	267.0	10.51	277.0	10.90	20.0	0.80	50.0	2.00	73.5	2.90	108.5	4.30	152.0	6.00	1

## **Machined sprocket**

Non standard material and color: See uni Material and Color Overview.





Please ensure that sufficient size shaft and keyway are chosen for corresponding load.

Other sprocket sizes are available upon request

Width of tooth: 15.0 mm/0.59 in Width of sprocket: 42.3 mm/1.67 in

uni Retainer Rings: See uni Retainer Ring data sheet















Expert advice and quality solutions for all your belting needs.

ammeraalbeltech.com

Ammeraal Beltech Modular A/S Hjulmagervej 21 DK-7100 Vejle T +31 7572 3100

ammega.com