Technical datasheet

Nitrile BX ES 10/3 01+C37 (NI) blue

Article code: LWCN560013



General information				
Product group	Light Weight Rubber			
Industry segment	Food: Meat & poultry; Paper & print; Automotive			
Indication of use	Slider bed, Rollers, In/declined conveying			
Belt construction				
Tension layer		RFL polyester spun, flexible		
Number of plies		3		
Top side	material	Nitrile BX, NX		
	finish	profile, C37 Supergrip profile		
	color	blue		
Bottom side	material	Nitrile, polyester		
	finish	smooth		
	color	black		

Technical data						
Hardness	ISO 868	top side	71A	Shore		
Force at 1% elongation	ISO 21181		10	N/mm	57.1	lbs/in.
Thickness	AB method KV.002	belt	7.4	mm	0.29	in.
		top cover	3.8	mm	0.15	in.
Weight	AB method KV.004		6.1	kg/m²	1.25	lbs/ft²
Operating temperature	continuous	from / to	-18 / 121	°C	-0.4 / 249.8	°F
	short	from / to	-18 / 135	°C	-0.4 / 275	°F
Minimum pulley diameter	flexing		65	mm	2.56	in.
	backflexing		150	mm	5.91	in.
Manufacturing width	standard		1829	mm	72.01	in.
	maximum		1829	mm	72.01	in.

Fabrication

Vulcanizing is always preferable. Cold splicing can only be done when the belt is exposed to normal temperature and the humidity is not excessive. For the working method, consult the splice information and the equipment literature. Apply the recommended splice as indicated in the seperate information.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.