

TT S09.16 C



Article code: FBTT054250

General information

Product group	High performance flat belts
Product sub type	Classic
Industry segment	General industry
Main product feature	Abrasion resistant, Low friction surface, Antistatic
Application	Drag band conveyor

Belt construction

Tension member		Polyamide foil
Top side	material	Polyamide fabric
	finish	Fabric textured
	color	black
Bottom / Pulley side	material	Polyamide fabric
	finish	Fabric textured
	color	black

Characteristics

Food Grade (FG)	no	
Anti-static (AS)	yes	
High conductive (HC)	no	

Technical data

Belt thickness	according to ISO 2286-3		1.65 mm	0.06 in.
Belt thickness tolerance		±	0.1 mm	0 in.
Weight	according to ISO 290703-1		1.65 kg/m ²	0.34 lbs/ft ²
Force at 1% elongation	according to ISO 21181	dynamic	9 N/mm	51.39 lbs/in.
Recommended elongation		min./max.	2 / 3 %	
Coefficient of friction, dynamic	according to ISO 21182	bottom side to steel	0.15	
		top side to steel	0.15	
Minimum pulley diameter	flexing		60 mm	2.36 in.
	back flexing		60 mm	2.36 in.
Operating temperature	continuous	from/to	0 / 80 °C	32 / 176 °F
Belt width	standard		570 mm	22.44 in.

Fabrication

Recommended splice method	WedgeSkive75D-1.5-2.8
---------------------------	-----------------------

Additional Information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F) and 65% relative humidity, unless otherwise stated, individual data may differ.

Consult our specialists for further instructions regarding joining, storage & maintenance, tracking & tensioning.

Consult our specialists for calculations with our E-RappCalc© technical calculation program.