

# Solicord V-belt TPU 90A White SM polyester

## 17x11

Article code: SCVB000043

### General information

|               |          |
|---------------|----------|
| Product group | SoliCord |
|---------------|----------|

### Construction

|                     |            |
|---------------------|------------|
| Material            | TPU        |
| (Top)surface finish | smooth     |
| Color               | white      |
| Shape               | Vee        |
| Execution           | reinforced |

### Characteristics

|                 |    |
|-----------------|----|
| Food Grade (FG) | no |
| Antistatic (AS) | no |
| ATEX approval   | no |

### Technical data

|                         |               |           |                        |              |
|-------------------------|---------------|-----------|------------------------|--------------|
| Hardness                | ISO 868       |           | 92A Shore              |              |
| Recommended pre-tension |               |           | 1.5 %                  |              |
| Working tension         |               |           | 40 daN/cm <sup>2</sup> |              |
| Diameter                |               |           | 0 mm                   | 0 in.        |
| Cross section           |               |           | 1.46 cm <sup>2</sup>   |              |
| Weight                  |               |           | 0.18 kg/m              | 0.04 lb/ft   |
| Operating temperature   | continuous    | from / to | -30 / 80 °C            | -22 / 176 °F |
| Minimum pulley diameter |               |           | 180 mm                 | 7.09 in.     |
| Coefficient of friction | against steel | dynamic   | 0,5                    |              |
|                         | against PE    |           | 0,3                    |              |
|                         | against HDPE  |           | 0,25                   |              |
| Manufacturing length    | maximum       |           | 50000 mm               | 1968.5 in.   |

### Fabrication

|                          |                                                                                                        |
|--------------------------|--------------------------------------------------------------------------------------------------------|
| Recommended splice types | overlap                                                                                                |
| Splice equipment         | Only use equipment supplied or approved by Ammeraal Beltech.                                           |
| Splicing on site         | Always first make a test splice to confirm the right settings and proper pre-heating of the equipment. |

### Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Keep the belt tension to a practical working minimum for maximum belt and machine life.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt.