

# Twister compression belt I.blue

## 1100x35x5.5

Article code: EBCO000008

### General information

<b>Product group</b>	Engineered belts, Compression Belt
<b>Industry segment</b>	Food; Container & packaging
<b>Main product feature</b>	Soft-grip

### Belt specifics

<b>Previous AB Item number</b>	CMM334
--------------------------------	--------

### Belt construction

<b>Base belt or substrate</b>	<b>type</b>	High performance flat belt	
	<b>tensionmember</b>	thermoplastic foil	
	<b>number of plies</b>	1	
<b>Intermediate layer</b>	<b>material</b>	polyurethane foam	
<b>Belt cover</b>	<b>material</b>	silicone rubber	
	<b>hardness</b>	35A	Shore
	<b>color</b>	Light blue	


### Characteristics

<b>Foodgrade (FG)</b>	<b>cover material</b>	yes	EC 1935/2004, EU 10/2011; Yes
<b>Oil &amp; fat resistant</b>		no	

### Technical data

<b>Belt</b>	<b>thickness</b>		5.5 mm	0.22 in.
	<b>length</b>		1100 mm	43.31 in.
	<b>width</b>		35 mm	1.38 in.
<b>Coefficient of friction</b>	<b>tooth side to steel</b>	dynamic	0,3	
<b>Operating temperature</b>	<b>continuous</b>	from / to	0 / 50 °C	32 / 122 °F
<b>Minimum pulley diameter</b>	<b>flexing</b>		50 mm	1.97 in.
	<b>backflexing</b>		not advised	

### General information



### Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.