Technical datasheet

Twister compression belt l.blue 1100x35x5.5



Article code: EBCO00008

General information	
Product group	Engineered belts, Compression Belt
Industry segment	Food; Container & packaging
Main product feature	Soft-grip


Belt specifics		
Previous AB Item number	C	CMM334

Belt construction				
Base belt or substrate	type	High performance flat belt		
	tensionmember	thermoplastic foil		
	number of plies	1		
Intermediate layer	material	polyurethane foam		
Belt cover	material	silicone rubber		
	hardness	35A	Shore	
	color	Light blue		

Characteristics			
Foodgrade (FG)	cover material	yes	EC 1935/2004, EU 10/2011; Yes
Oil & fat resistant		no	

Technical data						
Belt	thickness		5.5	mm	0.22	in.
	length		1100	mm	43.31	in.
	width		35	mm	1.38	in.
Coefficient of friction	tooth side to steel	dynamic	0,3			
Operating temperature	continuous	from / to	0 / 50	°C	32 / 122	°F
Minimum pulley diameter	flexing		50	mm	1.97	in.
	backflexing		not advised			

General information



Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.