

Soliflex CB TPU/30 Blue 900mm FG 2 rows 95A

Article code: SFPU001113

General information

Product group	Soliflex
Main product feature	Positive drive, Chemical resistant, Non-stick, Wear resistant

Belt construction

Material	TPU-M
Top side	Matte, Matte
Bottom side	smooth, Smooth+Lugs
Color	blue

Characteristics

Food Grade (FG)	yes	EU 1935/2004, EU 10/2011; FDA; No
------------------------	-----	-----------------------------------

Technical data

Pitch			39.7 mm	1.56 in.
Hardness	ISO 868		95A Shore	
Force at 1% elongation	ISO 21181		3.5 N/mm	19.99 lbs/in.
Belt thickness			3 mm	0.12 in.
Weight			4.6 kg/m ²	0.94 lbs/ft ²
Operating temperature	continuous	from / to	-20 / 60 °C	-4 / 140 °F
Minimum pulley diameter	flexing		100 mm	3.94 in.
	backflexing		100 mm	3.94 in.
Manufacturing width	maximum		900 mm	35.43 in.
	standard		900 mm	35.43 in.

Fabrication

Recommended splice method	Butt weld
----------------------------------	-----------

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Keep the belt tension to a practical working minimum for maximum belt and machine life.

Store loose and wrapped in plastic. The allowable product temperature may vary.

