

Nitrile ESM 14/2 0+C5 Green

Article code: LWN1560317

General information

Product group Light Weight Rubber

Belt construction

Tension layer		polyester spun, stable
Number of plies		2
Top side	material	Nitrile, Nitrile
	finish	C5 - Fabric Impression, C5 - Fabric Impression
	color	green
Bottom side	material	Nitrile, polyester spun
	finish	bare fabric
	color	brown

Characteristics

Food Grade (FG) yes FDA; USDA

Technical data

Hardness	ISO 868	top side	70A Shore		
Force at 1% elongation	ISO 21181		14 N/mm	79.94 lbs/in.	
Thickness	AB method KV.002	belt	2.8 mm	0.11 in.	
		top cover	0.8 mm	0.03 in.	
Weight	AB method KV.004		3.0 kg/m ²	0.61 lbs/ft ²	
		static	0,4		
		static	1,8		
Operating temperature	continuous	from / to	-18 / 121 °C	-0.4 / 249.8 °F	
	short	from / to	-18 / 121 °C	-0.4 / 249.8 °F	
Minimum pulley diameter	flexing		50 mm	1.97 in.	
	backflexing		100 mm	3.94 in.	
Manufacturing width	standard		1524 mm	60 in.	
	maximum		1524 mm	60 in.	

Fabrication

Vulcanizing is always preferable. Cold splicing can only be done when the belt is exposed to normal temperature and the humidity is not excessive. For the working method, consult the splice information and the equipment literature. Apply the recommended splice as indicated in the separate information.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.