

# LT S27 C

Article code: FBLT054050

## General information

<b>Product group</b>	High performance flat belts
<b>Product sub type</b>	Classic
<b>Industry segment</b>	General industry
<b>Main product feature</b>	Oil & grease resistant, Dusty environment
<b>Application</b>	Saw mills, Power transmission (crossed, cone drive)
<b>Indication of use</b>	Suitable for high start-up torques

## Belt construction

<b>Tension member</b>		Polyamide foil
<b>Top side</b>	<b>material</b>	Polyamide fabric
	<b>finish</b>	Fabric textured
	<b>color</b>	black
<b>Bottom / Pulley side</b>	<b>material</b>	Chrome leather
	<b>finish</b>	Ground quality
	<b>color</b>	grey

## Characteristics

<b>Food Grade (FG)</b>	no	
<b>Antistatic (AS)</b>	yes	
<b>High conductive (HC)</b>	no	

## Technical data

<b>Belt thickness</b>	ISO 2286-3		5.1 mm	0.2 in.
<b>Weight</b>	ISO 290703-1		5.6 kg/m <sup>2</sup>	1.15 lbs/ft <sup>2</sup>
<b>Force at 1% elongation</b>	ISO 21181	dynamic	27 N/mm	154.17 lbs/in.
<b>Recommended elongation</b>		min. / max.	2 / 3 %	
<b>Coefficient of friction, dynamic</b>	ISO 21182	bottom side to steel	0,25	
		top side to steel	0,15	
<b>Minimum pulley diameter</b>	flexing		350 mm	13.78 in.
	back flexing		350 mm	13.78 in.
<b>Operating temperature</b>	continuous	from / to	0 / 80 °C	32 / 176 °F
<b>Belt width</b>	standard		570 mm	22.44 in.

## Fabrication

<b>Recommended splice method</b>	WedgeSkive75D-2.8+
<b>Alternative splice method</b>	WedgeSkive90D-2.8+

## Fabrication

WedgeSkive75D-2.8+  
 WedgeSkive90D-2.8+

## Additional Information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.  
 Consult our specialists for further instructions regarding joining, storage & maintenance, tracking & tensioning.  
 Consult our specialists for calculations with our E-RappCalc® technical calculation program.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.