

Silam EZP 8/1 0+01 red HR / 10 mm

Article code: ZLSI583061

General information

Product group	ZipLink
Industry segment	Wood
Main product feature	Heat resistant
Indication of use	Slider bed, Rollers, Flat

Belt construction

Tension layer		Ziplink fabric, flexible
Number of plies		1
Top side	material	Silam, SI
	finish	smooth
	color	red
Bottom side	material	Mesh, polyester
	finish	smooth
	color	red

Characteristics

Antistatic (AS)	no
------------------------	----

Technical data

Force at 1% elongation	ISO 21181		8 N/mm	45.68 lbs/in.
Thickness	AB method KV.002		1.9 mm	0.07 in.
		top cover	0.1 mm	0 in.
Weight	AB method KV.004		1.75 kg/m ²	0.36 lbs/ft ²
Operating temperature	continuous	from / to	-40 / 180 °C	-40 / 356 °F
	short	from / to	-40 / 180 °C	-40 / 356 °F
Manufacturing width	standard		3300 mm	129.92 in.
	maximum		3800 mm	149.61 in.

Fabrication

Ziplink belts can be endlessed, very easy and quick splicing without presses, fasteners or glues. Refer to the technical information for more information about splicing of Ziplink belts.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.