

GG S22 LRC

Article code: FBGG054297

General information

| | |
|-----------------------------|------------------------------------|
| Product group | High performance flat belts |
| Product sub type | Classic |
| Industry segment | General industry |
| Main product feature | Shock absorbing |
| Application | Power transmission |
| Indication of use | Suitable for high start-up torques |

Belt construction

| | | |
|-----------------------------|-----------------|----------------------|
| Tension member | | Polyamide foil |
| Top side | material | NBR elastomer |
| | finish | Rough |
| | color | green |
| Bottom / Pulley side | material | NBR elastomer |
| | finish | Longitudinal grooves |
| | color | black |

Characteristics

| | | |
|-----------------------------|-----|----------|
| Food Grade (FG) | no | |
| Antistatic (AS) | yes | ISO 284 |
| High conductive (HC) | no | |
| | yes | ATEX III |

Technical data

| | | | | |
|---|-------------------|----------------------|-----------------------|-----------------------|
| Belt thickness | DIN EN ISO 2286-3 | | 4.6 mm | 0.18 in. |
| | tolerance | ± | 0.3 mm | 0.01 in. |
| Weight | ISO 290703-1 | | 4.9 kg/m ² | 1 lbs/ft ² |
| Force at 1% elongation | DIN EN ISO 21181 | dynamic | 22 N/mm | 125.62 lbs/in. |
| Recommended elongation | | min. / max. | 2 / 3 % | |
| Coefficient of friction, dynamic | DIN EN ISO 21182 | bottom side to steel | 0,6 μ | |
| | | top side to steel | 0,55 μ | |
| Minimum pulley diameter | flexing | | 220 mm | 8.66 in. |
| | back flexing | | 220 mm | 8.66 in. |
| Operating temperature | continuous | from / to | 0 / 80 °C | 32 / 176 °F |
| Belt width | standard | | 570 mm | 22.44 in. |

Fabrication

WedgeSkive75D-2.8+

Additional Information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Consult our specialists for further instructions regarding joining, storage & maintenance, tracking & tensioning.

Consult our specialists for calculations with our E-RappCalc© technical calculation program.

Our material, as well as the packaging, must be disposed of in a professional and environmentally friendly manner.

This item contain the following substance included on the candidate list according to article 59 (1, 10) of Regulation (EC) No 1907/2006 „REACH“ in a concentration above 0.1 % weight by weight: 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol [119-47-1]