

## Ultrascreen 3000 Light Blue FG

Article code: USBE000013

### General information

<b>Product group</b>	Ultrascreen
----------------------	-------------

### Belt construction

<b>Material</b>	TPE
<b>Color</b>	Light blue

### Product Characteristics

<b>Food Grade (FG)</b>	yes	According: all foodstuff
------------------------	-----	--------------------------

### Technical data

<b>Air permeability</b>	at $\Delta p=100$ Pa		6000	L/dm <sup>2</sup> /min		
<b>Mesh opening</b>			3000	$\mu$ m		
<b>Thickness</b>			1.85	mm	0.07	in.
<b>Weight</b>			0.61	kg/m <sup>2</sup>	0.12	lbs/ft <sup>2</sup>
<b>Operating temperature</b>	continuous	from/to	-15 / 25	°C	5 / 77	°F
	short	from/to	-15 / 50	°C	5 / 122	°F
<b>Minimum pulley diameter</b>	flexing		100	mm	3.94	in.
	backflexing		100	mm	3.94	in.
<b>Belt length</b>	maximum		100000	mm	3937.01	in.
<b>Belt width</b>	standard		2000	mm	78.74	in.
	maximum		4000	mm	157.48	in.

### Fabrication

<b>Edge finish</b>	To improve the stability of Ultrascreen belts, homogeneous strips could be mounted longitudinally. Strips are available in: <ul style="list-style-type: none"> <li>- Flexam PVC</li> <li>- Amtel TPE</li> </ul>
<b>Tracking</b>	To improve tracking on Ultrascreen belts, belts could be fitted with ropes. The following rope could be fitted: <ul style="list-style-type: none"> <li>- Rope Vee Solid 13x8 Flexam PVC light blue</li> </ul>
<b>Available accessoires</b>	The following cleats are possible to be fitted: <ul style="list-style-type: none"> <li>- Amtel TPE-E 90°</li> <li>- Ropanyl TPU 90° - 70°</li> </ul> <p>To avoid sideway spiledge, Bordoflex sidewalls could be fitted, which are available in:</p> <ul style="list-style-type: none"> <li>- Amtel TPE-E</li> <li>- Flexam PVC</li> </ul>
<b>Endlessing</b>	The following methods are used to endless the belt: <ul style="list-style-type: none"> <li>- Stainless steel fastener</li> <li>- Plastic fastener</li> <li>- Endless splice</li> </ul>

### Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ. Keep the belt tension to a practical working minimum for maximum belt and machine life.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging. The allowable product temperature may vary.

Consult our specialists in case of questions or remarks.