

## GG S09.22 RFC

Article code: FBGG054733



## General information

<b>Product group</b>	High performance flat belts
<b>Product sub type</b>	Classic
<b>Industry segment</b>	Textile; Logistics
<b>Main product feature</b>	Shock absorbing
<b>Application</b>	Power transmission
<b>Indication of use</b>	High efficient rubber cover

## Belt construction

<b>Tension member</b>		Polyamide foil
<b>Top side</b>	<b>material</b>	XNBR elastomer
	<b>finish</b>	Fine
	<b>color</b>	blue
<b>Bottom / Pulley side</b>	<b>material</b>	XNBR elastomer
	<b>finish</b>	Rough
	<b>color</b>	grey

## Characteristics

<b>Food Grade (FG)</b>	no
<b>Anti-static (AS)</b>	yes
<b>High conductive (HC)</b>	no

## Technical data

<b>Belt thickness</b>	according to ISO 2286-3		2.2 mm	0.09 in.
	tolerance	±	0.2 mm	0.01 in.
<b>Weight</b>	according to ISO 290703-1		2.5 kg/m <sup>2</sup>	0.51 lbs/ft <sup>2</sup>
<b>Force at 1% elongation</b>	according to ISO 21181	dynamic	9 N/mm	51.39 lbs/in.
	according to ISO 527	static	30 N/mm	171.3 lbs/in.
<b>Recommended elongation</b>		min./max.	2 / 3 %	
<b>Coefficient of friction, dynamic</b>	according to ISO 21182	bottom side to steel	0.6	
		top side to steel	0.6	
<b>Minimum pulley diameter</b>	flexing		60 mm	2.36 in.
	back flexing		60 mm	2.36 in.
<b>Operating temperature</b>	continuous	from/to	0 / 80 °C	32 / 176 °F
<b>Belt width</b>	standard		570 mm	22.44 in.

## Fabrication

<b>Recommended splice method</b>	WedgeSkive75D-1.5-2.8
----------------------------------	-----------------------

### **Additional Information**

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F) and 65% relative humidity, unless otherwise stated, individual data may differ.

Consult our specialists for further instructions regarding joining, storage & maintenance, tracking & tensioning.

Consult our specialists for calculations with our E-RappCalc© technical calculation program.