

Soliflex PRO mini TPU/20 white FG Mono

Article code: SFPU000746

General information

Product group	Soliflex
Main product feature	Positive drive, Chemical resistant, Non-stick, Wear resistant

Belt construction

Material		TPU
Top side	finish	smooth
Bottom side	finish	smooth
Color		white

Characteristics

Food Grade (FG)	yes	According to: EU 1935/2004, EU 10/2011; FDA; USDA
------------------------	-----	---

Technical data

Pitch			25.5 mm	1 in.
Hardness	according to ISO 868		53D Shore	
Belt thickness			2 mm	0.08 in.
Weight			2.4 kg/m ²	0.49 lbs/ft ²
Force at 1% elongation	according to ISO 21181		2 N/mm	11.42 lbs/in.
Operating temperature	continuous	from/to	-5 / 70 °C	23 / 158 °F
Minimum pulley diameter	flexing		63.3 mm	2.49 in.
	backflexing		79.6 mm	3.13 in.
Belt width	maximum		1200 mm	47.24 in.

Fabrication

Recommended splice method	Butt weld
----------------------------------	-----------

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Keep the belt tension to a practical working minimum for maximum belt and machine life.

Store loose and wrapped in plastic. The allowable product temperature may vary.

