Technical datasheet

MSB329 AmSqueeze 714 A18-A21 1330x205x13.4mm



Article code: EWMS000374

General information	
Product group	endless woven
Industry segment	Food: Meat & poultry
Main product feature	Foodgrade, Abrasion resistant, Oil & grease resistant, Cut resistant
Application	Soft Separator
Indication of use	Special fine structured surface, Abrasive applications

Belt construction				
Tension layer		polyester		
Number of plies		1		
Top side	material	Ropanyl, TPU		
	finish	profile, A21 Fine diamond profile		
	color	transparent		
Bottom side	material	Ropanyl, TPU		
	finish	profile, A18 Fine square profile		
	color	white		

Characteristics		
Food Grade (FG)	yes	EC 1935/2004, EU 10-2011; FDA
Antistatic (AS)	no	
Flame-retardant (FR)	no	

Technical data						
Hardness	ISO 868	top side	93A	Shore		
		bottom side	85A	Shore		
Force at 1% elongation	ISO 21181		28	N/mm	159.88	lbs/in.
Thickness		total	13.4	mm	0.53	in.
		top cover	5.4	mm	0.21	in.
		bottom cover	5.4	mm	0.21	in.
Weight			21.8	kg/m²	4.46	lbs/ft²
Length		from / to	1330	mm		in.
Width		from / to	205	mm		in.
Operating temperature	continuous	from / to	-20 / 90	°C	-4 / 194	°F
	short	from / to	-30 / 110	°C	-22 / 230	°F
Minimum pulley diameter			134	mm	5.28	in.

Tolerances				
Length	± 1 %	minimum ±	20 mm	0.79 in.
Width		from / to	-0 / +2 mm	-0 / +0.08 in.
Thickness		±	0.2 mm	0.01 in.

Side view



Belt type	AmSqueeze 300 series	AmSqueeze 500 series	AmSqueeze 700 series	
	. 2. 2. A. C.	33.0.0.	7 A 3 A	
Example article description	AS 314 A93-A93	AS 514 A93-A93	AS 714 A93-A93	
Top cover material	TPU 3 mm Ropanyl FG	TPU 3 mm Ropanyl FG	TPU 3 mm Ropanyl FG	
Top cover color	Ivory	White	Transparent	
Top cover hardness	76° Shore A	85° Shore A	93° Shore A	
Standard finish covers	A93 Rhombus profile	A93 Rhombus profile	A93 Rhombus profile	
Standard belt thickness	13.4	13,4	13.4	
Other available belt thickness [mm]	15,16,17,18,19,20	15,16,17,18	15,16,17,18	
Grip	++++	++++	+++	
Wear resistance	+++	++++	++++	
Yield	++++	++++	+++	
Food Grade	EC/FDA	EC/FDA	EC/FDA	
Consult our application engineers and product information for other options. Tolerance on length $\pm 1\%$ Width $-0/+2$ mm.				

Tolerance on length $\pm 1\%$ Width -0/+2 mm

Closed edges skived.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.