

Flexam EM 8/2 0+04 dark green AS FG

Article code: SBFL881920

General information

Product group	Synthetic Belts
Main product feature	Antistatic, Foodgrade

Belt construction

Number of plies		2
Top side	material	Flexam, PVC
	color	dark green
Bottom side	material	fabric

Characteristics

Food Grade (FG)	yes	
Antistatic (AS)	yes	ISO 21178
High conductive (HC)	no	
Flame-retardant (FR)	no	
ATEX approval	no	

Technical data

Hardness	ISO 868	top side	80A Shore		
Thickness	AB method KV.002	total	1.90 mm	0.07 in.	
Weight	AB method KV.004		0 kg/m ²	0 lbs/ft ²	

Fabrication

Hot splicing is always preferable. Glueing can only be done when the belt is exposed to normal temperature and the humidity is not excessive. For the working method, consult the splice information and the equipment literature. Apply the recommended splice as indicated in the separate information.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.