




Plastic Modular Belt

Series **uni Light** Type **10% Open**



Straight running belt
Nominal pitch: 19.1 mm (0.75 in)
Surface type: Flat
Surface opening: 10%
Backflex radius: 25.0 mm (2.0 in)
Pin diameter: 5.0 mm (0.20 in)

Belt material & color	POM-LF BR		mm	in		mm	in
Pin material & color	 PP W	P (Nominal)	19.1	0.75	T	8.5	0.33
		L	4.3	0.17	-	-	-

Non standard material and color: See uni Material and Color Overview.

Belt width		Permissible tensile force (Belt/pin material)		Belt weight (Belt/pin material)		*Min. No. drive sprocket per shaft	Number of wear strips (Min. No.)	
		POM-LF/PP		POM-LF/PP			**Carry (pcs)	**Return (pcs)
mm	in	N	lbf	kg/m	lb/ft			
77	3.0	789	177	0.5	0.32	2	2	2
115	4.5	1175	264	0.7	0.48	2	2	2
153	6.0	1572	353	1.0	0.64	2	2	2
230	9.0	2355	529	1.4	0.96	2	2	2
306	12.1	3138	705	1.9	1.28	3	3	2
383	15.1	3921	881	2.4	1.59	3	3	2
459	18.1	4704	1057	2.8	1.91	4	4	2
535	21.1	5486	1233	3.3	2.23	4	4	2
612	24.1	6269	1409	3.8	2.55	5	5	3
688	27.1	7052	1585	4.3	2.87	5	5	3
764	30.1	7835	1761	4.7	3.19	6	6	3
841	33.1	8618	1937	5.2	3.50	6	6	3
917	36.1	9401	2113	5.7	3.82	7	7	4

Additional standard belt widths are available in steps of 76.4 mm (3.01 in). Additional non-standard belt widths are available in steps of 19.1 mm (0.75 in).

1910	75.2	19578	4401	11.8	7.96	13	13	7
------	------	-------	------	------	------	----	----	---

Additional standard belt widths are available in steps of 76.4 mm (3.01 in). Additional non-standard belt widths are available in steps of 19.1 mm (0.75 in).

2980	117.3	30545	6867	18.5	12.42	20	20	10
------	-------	-------	------	------	-------	----	----	----

General belt tolerance is +0/-0.4% at 23°C/73°F and 50% RH. For exact belt width contact Customer Service. Non standard belt width on request.


*Max. Load per Drive Sprocket. Belt material: POM-LF 1250 N

**Max. Spacing between wear strips, Carry: 152.0 mm (6.00 in); Return: 304.0 mm (12.00 in).

= Single Link

Accessories

Rubber Top



Type	Belt Material & color	Rubber Material & color	A		B		C		Link size	Width	
			mm	in	mm	in	mm	in		mm	in
NON STANDARD Flat	PP K	03 K	2.0	0.08	2.0	0.08	-	-	K300	76.0	2.99
STANDARD Rough							1.0	0.04	K450	114.0	4.49
									K600	150.5	5.93

Indent 15.0 mm (0.59 in) is only available in size 228.6 mm (9.00 in) and wider.

Accessories

Flight




Type	Flight Material & color		H		Link size	Width		Indent	
			mm	in		mm	in	mm	in
Non Stick	PP-I	W	25.4	1.00	K300	76.4	3.01	0.0	0.00
	PP-I	W G			K600	152.8	6.02	0.0	0.00
	PA6	K							
	04	K							
Non Stick	PP-I	W G	25.4	1.00	K600	152.8	6.02	15.0	0.59
Non Stick/Support Ribs	PP-I	W	25.4	1.00	K600	152.8	6.02	0.0	0.00
Non Stick/Support Ribs	PP-I	W G	50.8	2.00	K600	152.8	6.02	0.0	0.00
	PA6	K							
Non Stick/Support Ribs	PP-I	G	50.8	2.00	K600	152.8	6.02	15.0	0.59
	PA6	K							
Non Stick/Support Ribs	PP-I	W G	76.2	3.00	K600	152.8	6.02	0.0	0.00
	04	K							
Non Stick/Support Ribs	PP-I	W G	76.2	3.00	K600	152.8	6.02	15.0	0.59

Other Non Standard material and color: See uni Material and Color Overview.

Accessories

Side Guard




Type	Side Guard Material & color	H		A		B	
		mm	in	mm	in	mm	in
Closed	PP-I W G	31.4	1.24	15.0	0.59	25.0	0.98

Non Standard material and color: See uni Material and Color Overview.

Accessories

Tab



Type	Tab Material & color	G		J		K		H	
		mm	in	mm	in	mm	in	mm	in
Bottom Hold Down	POM-D N	3.5	0.14	20.0	0.79	11.7	0.46	15.9	0.63

Non Standard material and color: See uni Material and Color Overview.


Sprocket

No of teeth	Bore size										Overall diameter		Pitch-diameter		Hub-diameter		A-dimen-sion		B-dimen-sion		Single row/Two way	PA6 LG
	Pilot bore	in	0.75	0.78	0.98	1.00	1.18	1.25	1.50	1.57												
		mm	19.1	20.0	25.0	25.4	30.0	31.8	38.1	40.0	mm	in	mm	in	mm	in	mm	in	Molded			
Z07	✔		●	●						42.6	1.68	43.9	1.73	30.0	1.18	15.4	0.61	26.3	1.04	✔	✔	
Z10	✔					●	●			61.7	2.43	61.6	2.43	45.0	1.77	25.0	0.98	35.2	1.39	✔	✔	
Z17	✔				●	●	●	■	■	105.0	4.13	103.7	4.08	65.0	2.56	46.6	1.83	56.2	2.21	✔	✔	
Z24	✔					●	●	●	■	●	147.2	5.80	146.0	5.75	70.0	2.76	68.0	2.68	77.3	3.04	✔	✔
Z25	✔						●	●	●	■	153.3	6.04	152.0	5.98	70.0	2.76	71.0	2.80	80.3	3.16	✔	✔

■ Molded sprocket



● Molded sprocket



Other sprocket sizes are available upon request.
Two-part sprocket are available upon request.
Round bores are always delivered with keyway.
Other bore sizes are available upon request.
uni Retainer Rings: See uni Retainer Ring data sheet.
Width of tooth = 4.8 mm (0.19 in)
Width of sprocket = 25.0 mm (0.98 in)

Max load per sprocket shown does not take bore size into account.
Please also ensure that sufficient size shaft is chosen for corresponding load.

For correct sprocket position: See uni Assembly Instructions for uni Light.
For more detailed sprocket information, contact Customer Service.

Non standard material and color: See uni Material and Color Overview.


uni Light 10% Open/2018.03.14



Synthetic Belts



Endless Woven Belts



Modular Belts



Engineered Belts



Homogeneous Belts



Fabrication & Service

Expert advice and quality solutions
for all your belting needs.
ammeraalbeltech.com

Ammeraal Beltech Modular A/S
Hjulgagervej 21
DK-7100 Vejle
T +31 7572 3100

ammerga.com

This information is subject to alteration due to continuous development. Ammeraal Beltech will not be held liable for the incorrect use of the above stated information. This information replaces previous information. All activities performed and services rendered by Ammeraal Beltech are subject to general terms and conditions of sale and delivery, as applied by its operating companies.

Member of Ammega Group.