Technical datasheet

Solicord Round TPU 75A Sky Blue SM FG hollow 125

Article code: SCRB000176

General information

Product group	SoliCord

Construction

Material	TPU
(Top)surface finish	smooth
Color	sky blue
Shape	round
Execution	hollow

Characteristics

Food Grade (FG)	yes	all foodstuff; all foodstuff
Antistatic (AS)	no	
ATEX approval	no	

Technical data

Hardness	ISO 868		80A	Shore		
Recommended pre-tension			6-8	%		
Working tension			12	daN/cm²		
Diameter			12.5	mm	0.49	in.
Cross section			1.02	cm²		
Weight			0.124	kg/m	0.03	lb/ft
Operating temperature	continuous	from / to	-30 / 80	°C	-22 / 176	°F
Minimum pulley diameter			85	mm	3.35	in.
Coefficient of friction	against steel	dynamic	0,7			
	against PE		0,4			
	against HDPE		0,35			
Manufacturing length	maximum		50000	mm	1968.5	in.

Fabrication

Recommended splice types	nipple fastener
Splice equipment	Only use equipment supplied or approved by Ammeraal Beltech.
Splicing on site	Always first make a test splice to confirm the right settings and proper pre-heating of the equipment.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Keep the belt tension to a practical working minimum for maximum belt and machine life.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.