Technical datasheet

PTFE DXL-06 Fibreglass



Article code: PPFD000004

General information							
Product group	Peak Products	Peak Products					
Belt construction							
Fabric tension layer	Fibreglass						
Color	Copper						
Characteristics							
Food Grade (FG)	yes	yes Yes; Yes; Ye					
Antistatic (AS)	no						
Technical data							
Belt thickness				0.15	mm	0.01	in.
Weight				0.292	kg/m²	0.06	lbs/ft²
PTFE content				63.4	%		
Operating temperature	continuous		from / to	-73 / 260	°C	-99.4 / 500	°F
	short		from / to	-73 / 300	°C	-99.4 / 572	٩F
Manufacturing length	maximum			100000	mm	3937.01	in.
Manufacturing width	standard			1000	mm	39.37	in.
	maximum			1000	mm	39.37	in.
Fabrication							
Recommended splice method	Peak Products						
Additional information							

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ. Keep the belt tension to a practical working minimum for maximum belt and machine life.

Store loose and wrapped in plastic. The allowable product temperature may vary.

Consult our specialists is case of questions or remarks.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.