

UV N12 SQ

Article code: FBUV054560

General information

Product group	High performance flat belts
Product sub type	QuickSplice
Industry segment	Paper & print; Postal automation
Main product feature	Elastic
Application	Paper processing, Printing & finishing, Mail handling
Indication of use	Bi-directional, Gentle cover for delicate papers

Belt construction

Tension member		Polyurethane
Top side	material	Fleece
	finish	Ground quality
	color	grey
Bottom / Pulley side	material	Polyurethane
	finish	Fine
	color	Royal blue

Characteristics

Food Grade (FG)	no	
Antistatic (AS)	yes	
High conductive (HC)	no	
ATEX approval	no	

Technical data

Belt thickness	ISO 2286-3		1.5 mm	0.06 in.
Weight	ISO 290703-1		1.7 kg/m ²	0.35 lbs/ft ²
Force at 6% elongation	ISO 21181	dynamic	1.2 N/mm	6.85 lbs/in.
	ISO 527	static	4 N/mm	22.84 lbs/in.
Recommended elongation		from / to	0.5 / 1.5 %	
Coefficient of friction, dynamic	ISO 21182	bottom side to steel	0,2 μ	
		top side to steel	0,2 μ	
Minimum pulley diameter	flexing		20 mm	0.79 in.
	back flexing		20 mm	0.79 in.
Operating temperature	continuous	from / to	0 / 60 °C	32 / 140 °F
Belt width	standard		1200 mm	47.24 in.

Fabrication

Recommended splice method	QuickSplice30
----------------------------------	---------------

Additional Information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Consult our specialists for further instructions regarding joining, storage & maintenance, tracking & tensioning.

Consult our specialists for calculations with our E-RappCalc® technical calculation program.

Our material, as well as the packaging, must be disposed of in a professional and environmentally friendly manner.