

SBR EF 16/2 00+C52 black CR HR FR

Article code: LWSB560447

General information

Product group	Light Weight Rubber
Main product feature	Cold resistant, Foodgrade, Heat resistant

Belt construction

Number of plies		2
Top side	material	SBR, SB
	finish	profile, C52 Diamond impression profile
	color	black
Bottom side	material	fabric, polyester
	finish	bare fabric

Technical data

Thickness	AB method KV.002	belt	7.8 mm	0.31 in.
Operating temperature	continuous	from / to	-40 / 121 °C	-40 / 249.8 °F
	short	from / to	-40 / 121 °C	-40 / 249.8 °F
Manufacturing width	standard		1829 mm	72.01 in.

Fabrication

Vulcanizing is always preferable. Cold splicing can only be done when the belt is exposed to normal temperature and the humidity is not excessive. For the working method, consult the splice information and the equipment literature. Apply the recommended splice as indicated in the separate information.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ. We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts. Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging. For details consult 'Storage and handling instructions' or contact our specialist.